HTM2D





Designed to partner the 803D, and even the 802/801/800 models when space restrictions preclude the larger HTMD, the HTM2D features the phenomenal diamond dome tweeter in a full 3-way centre speaker. In the main Matrix[™] cabinet, the Kevlar® cone FST[™] midrange driver is accompanied by two 7" bass drivers, their Rohacell® sandwich cones combining with twin, rear-facing Flowports[™] to ensure great dynamics and control.

Thanks to its magnetic shielding, the HTM2D can be placed close to CRT-based TVs and rear projectors, on either a custom shelf or the FS-HTM floor stand. This stand supports the speaker at a height low enough to allow the use of large projector screens that come to within 2 ft. of the floor and has zero, 4 or 8 degrees of tilt back so that the speaker can be directed towards the listeners.

Description:	3-way vented-box system	No
Frequency Range:	-6dB at 35Hz and 33kHz	Dii
Frequency Response:	41Hz – 28kHz ±3dB on reference axis	We
Sensitivity:	90dB spl (2.83V, 1m)	Fir

Nominal Impedance:	8Ω (minimum 3.1Ω)
Dimensions:	H 329mm W 841mm D 387mm H 13" W 33.1" D 15.2"
Weight:	31 kg / 68 lbs.
Finishes:	Cherrywood, Rosenut, Black Ash

B&W Bowers & Wilkins

B&W Group Ltd Dale Road Worthing West Sussex BN11 2BH England

T +44 (0) 1903 221800 F +44 (0) 1903 221801 info@bwgroup.com www.bwspeakers.com

UK Group (UK Sales) T +44 1903 221 500 E uksales@bwgroup.com B&W Group North America T +1 978 664 2870 E marketing@bwgroupusa.com B&W Group Asia Ltd T +852 2 869 9916 E showroom@bwgroup.hk