Bowers & Wilkins

800 Series HTM2 Diamond



A Legend Reborn

The HTM2 Diamond is an ideal centre-channel dialogue speaker to use as part of an 800 Series Diamond home theatre set up, providing all the clarity and richness you need for larger viewing spaces, courtesy of two dedicated bass drivers, an FST midrange driver and a diamond tweeter.

Technical Specifications

Technical features	Free-mounted diamond dome tweeter Nautilus™ tube tweeter loading Quad magnet tweeter motor Kevlar® brand fibre cone FST™ midrange Rohacell® cone bass Dual magnet bass driver motor Matrix™ cabinet Flowport™				
Description	3-way vented-box system				
Drive units	1x ø25mm (1 in) diamond dome high-frequency 1x ø150mm (6 in) woven Kevlar® cone FST™ midrange 2x ø180mm (7 in) Rohacell® cone bass				
Frequency range	-6dB at 35Hz and 33kHz				
Frequency response	41Hz - 28kHz ±3dB on reference axis				
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc				
Sensitivity	90dB spl (2.83V, 1m)				
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 80Hz - 100kHz <0.5% 100Hz - 100kHz				
Nominal impedance	8Ω (minimum 3.1Ω)				
Crossover frequency	350Hz, 4kHz				
Recommended amplifier power	50W - 300W into 8Ω on unclipped programme				
Max. recommended cable impedance	0.1Ω				
Dimensions	Height: Width: Depth:	329mm (13 in) 841mm (33.1 in) 387mm (15.2 in)			
Net weight	31kg (68 l	31kg (68 lb)			
Finish	Cabinet:	Cherrywood	Rosenut	Piano Black Gloss	



Black cloth



www.bowers-wilkins.com

Kevlar is a registered trademark of DuPont. Nautilus is a trademark of B&W Group Ltd. Rohacel is a trademark of Evonik Röhm GMbH Flowport and Matrix are trademarks of B&W Group Ltd. Copyright © B&W Group Ltd. E&OE B&W Group Ltd reserves the right to amend details of the specification without notice in line with technical developments