Bowers & Wilkins

800 Series





A Legend Reborn

Perfect for smaller viewing areas, the HTM4 Diamond centre-channel speaker will seamlessly balance the sound in an 800 Diamond home theatre set-up, thanks to highly advanced, complementary technology like a Kevlar bass/midrange driver and – for the first time ever – a diamond dome tweeter unit.

Technical Specifications

Technical features	Free-mounted diamond dome tweeter Nautilus™ tube tweeter loading Quad magnet tweeter motor Kevlar® brand fibre cone bass/midrange Matrix™ cabinet Flowport™	
Description	2-way vented-box system	
Drive units	1x ø25mm (1 in) diamond dome high-frequency 1x ø165mm (6.5 in) woven Kevlar® cone bass/midrange	
Frequency range	-6dB at 42Hz and 33kHz	
Frequency response	49Hz - 28kHz \pm 3dB on reference axis	
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc	
Sensitivity	88dB spl (2.83V, 1m)	
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 100kHz <0.5% 150Hz - 100kHz	
Nominal impedance	8Ω (minimum 4.7Ω)	
Crossover frequency	4kHz	
Recommended amplifier power	50W - 120W into 8Ω on unclipped programme	
Max. recommended cable impedance	0.1Ω	
Dimensions	Height: Width: Depth:	279mm (11 in) 486mm (19.1 in) 287mm (11.3 in)
Net weight	12.5kg (27 lb)	
Finish	Cabinet:	1

Grilles:



Black cloth

Bowers & Wilkins

www.bowers-wilkins.com

Kevlar is a registered trademark of DuPont. Nautilus is a trademark of B&W Group Ltd. Flowport and Matrix are trademarks of B&W Group Ltd. Copyright © B&W Group Ltd. E&OE B&W Group Ltd reserves the right to amend details of the specification without notice in line with technical developments