## Custom Installation CCM7.3



## See nothing, hear everything

The CCM7.3 is a 3-way speaker that features a 25mm(1in) soft dome tweeter, 100mm (4in) FST<sup>™</sup> Kevlar<sup>®</sup> mid-range and 2 x 130mm (5in) bass drivers. With the bass and mid-range drivers set in a die-cast chassis the CCM7.3 incorporates some of the proven technologies from the CT700 Series alongside new additions such as a critically formed baffle constructed from glass reinforced ABS. The baffle features a scallop under the tweeter which creates the perfect roll off for high frequencies resulting in a more accurate reproduction of sound.

## **Technical Specifications**

Description	3-way in-ceiling system		
Drive Units	1x ø25mm (1in) Nautilus <sup>™</sup> tube loaded soft dome tweeter 1x ø100mm (4in) blue Kevlar® cone FST <sup>™</sup> midrange 2x ø130mm (5in) paper/Kevlar® cone bass drivers		
Frequency Range (-6dB)	52Hz – 28kHz		
Recommended Amp Power	25 – 200w		
Sensitivity SPL (2.83V, 1m)	90 dB		
Impedance Nominal (min)	6Ω (3.5Ω)		
Frame height	355mm (14in)		
Frame width	355mm (14in)		
Depth	194.5mm (7.66in)		
Cut-out height	332mm (13.1in)		
Cut-out width	332mm (13.1in)		
Cut-out height w/PMK	335mm (13.2in)		
Cut-out width w/PMK	335mm (13.2in)		
Protrusion	8mm (0.3in)		
РМК	7C		

## Bowers & Wilkins

www.bowers-wilkins.com

Nautilus, Flowport and FST are trademarks of B&W Group Ltd. Kevlar is a registered trademark of DuPont. Copyright © B&W Group Ltd. E&OE

