



See nothing, hear everything

The CCM7.5 features a 150mm(6in) bass/mid-range driver in a die-cast chassis and a Nautilus™ tube loaded 25mm (1in) soft dome tweeter. Its baffle is critically formed from glass reinforced ABS and features a scallop under the tweeter which creates the perfect roll off for high frequencies resulting in a more accurate reproduction of sound.

Technical Specifications

Description 2-way in-ceiling system

Drive Units 1x ø25mm (1in) Nautilus™ tube loaded soft dome tweeter

1x Ø150mm (6in) blue Kevlar® cone bass/midrange

Frequency Range (-6dB)56Hz - 28kHzRecommended Amp Power25 - 150wSensitivity SPL (2.83V, 1m)88 dBImpedance Nominal (min)8Ω (6.5Ω)

 Frame height
 355mm (14in)

 Frame width
 355mm (14in)

 Depth
 194.5mm (7.66in)

 Cut-out height
 332mm (13.1in)

 Cut-out width
 332mm (13.1in)

 Cut-out height w/PMK
 335mm (13.2in)

 Cut-out width w/PMK
 335mm (13.2in)

Protrusion 8mm (0.3in)

PMK 7C

Bowers & Wilkins

www.bowers-wilkins.com

Nautilus, Flowport and FST are trademarks of B&W Group Ltd.
Kevlar is a registered trademark of DuPont. Copyright © B&W Group Ltd. E&OE

