### Bowers & Wilkins

### CM Series



# CM9 S2

CM9 S2 delivers a supremely wellintegrated sound, and is capable of filling the largest of listening rooms with a coherent, insightful performance. It is a speaker with wonderful power, presence and naturalness, thanks to its two large bass units, FST midrange and Decoupled Double Dome tweeter. It is also just a much at home as the front speakers in a breathtaking home theatre system.

### Bowers & Wilkins

## CM9 S2



Technical features	Nautilus tube loaded Decoupled Double Dome aluminium tweeter Kevlar <sup>®</sup> brand fibre cone FST midrange Flowport™
Description	3-way vented-box system
Drive units	1x ø25mm (1 in) Decoupled Double Dome aluminium high-frequency 1x ø150mm (6 in) woven Kevlar cone FST midrange 2x ø165mm (6.5 in) paper/Kevlar cone bass
Frequency range	-6dB at 30Hz and 50kHz
Frequency response	9 46Hz - 28kHz ±3dB
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc
Sensitivity	89dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 90Hz - 22kHz <0.5% 120Hz - 20kHz
Nominal impedance	8Ω (minimum 3Ω)
Crossover frequency	350Hz, 4kHz
Recommended amplifier power	30W - 200W into $8\Omega$ on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 990mm (39 in) cabinet only
	1025mm (40.4 in) including plinth but not feet Width: 200mm (7.9 in) cabinet only 320mm (12.6 in) including plinth
	Depth: 300mm (11.8 in) cabinet only 321mm (12.6 in) inc. grille and terminals but not plinth 370mm (14.6 in) including plinth
Net weight	26.6kg (58.5 lb)
Finishes	Cabinet: Grille: Rosenut Black Gloss Black Black

Satin White

Grey