

TECHNICAL SPECIFICATIONS

SPEKTOR	1	2	6	VOKAL
Frequency Range [+/- 3]	59 - 26,000 Hz	54 - 26,000 Hz	43 - 26,000 Hz	66 - 26,000 Hz
Sensitivity [2.83V/1m]	83.0 dB	84.5 dB	88.5 dB	87.0 dB
Nominal Impedance	6 ohms	6 ohms	6 ohms	6 ohms
Maximum SPL	103 dB	105 dB	109 dB	107 dB
Recommended Amplifier Power	40 - 100 Watt	25 - 100 Watt	30 - 150 Watt	40 - 120 Watt
Crossover Frequency	2,100 Hz	2,600 Hz	2,500 Hz	2,100 Hz
Crossover Principle	2-way	2-way	2-way	2-way
High Frequency Driver	1 x 21 mm soft dome	1 x 25 mm soft dome	1 x 25 mm soft dome	1 x 25 mm soft dome
Low Frequency/midrange Driver(s)	1 x 4½"	1 x 5¼"	2 x 6½"	2 x 4½"
Enclosure Type	Bass Reflex	Bass Reflex	Bass Reflex	Bass Reflex
Bass Reflex Tuning Frequency	58.0 Hz	51.5 Hz	41.0 Hz	51.5 Hz
Connection Input(s)	Single	Single	Single	Single
Recommended Placement	Stand/ Shelf/Wall	Stand/ Shelf/Wall	Floor	Shelf
Recommended Distance from rear wall to speaker's rear panel	1 - 50 cm	1 - 80 cm	20 - 100 cm	1 - 50 cm
Dimensions (H x W x D)	237 x 140 x 195 mm	292 x 170 x 238 mm	972 x 195 x 313 mm	152 x 435 x 204 mm
	9.33 x 5.51 x 7.68 in	11.50 x 6.69 x 9.37 in	38.28 x 7.68 x 12.32 in	5.98 x 17.13 x 8.03 in
Weight	2.6 kg	4.2 kg	13.8 kg	5.3 kg
	5.73 lb	9.26 lb	30.42 lb	11.68 lb
Accessories	Rubber feet, manual, wall bracket	Rubber feet, manual, wall bracket	Spike set, rubber feet, manual	Rubber feet, manual

All technical specifications are subject to change without notice.